
AD-A035 965

UNCLASSIFIED

UNCLASSIFIED

AD-A035 965

AD-A035 96



WEIDLINGER ASSOCIATES

110 EAST 59TH STREET

NEW YORK, NEW YORK 10022

NUMERICAL ANALYSIS OF THE DYNAMIC RESPONSE OF

ELASTO-PLASTIC SHELLS

by


M.P. Bieniek, J. Funaro and M.L. Baron

# COPY AVAILABLE TO DDC DDES NOT PERMIT FULLY LEGIBLE PRODUCTION

TECHNICAL REPORT No. 20

NOVEMBER 1976

OFFICE OF NAVAL RESEARCH
CONTRACT No. NOO014-72-C-0119



This project is sponsored by the joint DNA/ONR/NAVSEA program in "Advanced Submarine Shock Survivability in Underwater Nuclear Attack."

Approved for public release; Distribution unlimited.

# TABLE OF CONTENTS

	PAGE
NOMENCLATURE	i
I INTRODUCTION	1
II BASIC SHELL EQUATIONS	4
III SHELL CONSTITUTIVE EQUATIONS	6
IV DISCRETIZATION	10
V EQUATIONS OF MOTION	13
VI INTEGRATION IN TIME	14
VII SMALL STIFFENERS	15
VIII LARGE STIFFENERS	17
IX IMPLEMENTATION	18
X CONCLUSIONS	20
REFERENCES	21
FIGURES	22



# ABSTRACT

An efficient numerical procedure for the transient dynamic analysis of elasto-plastic shells is introduced. A simple shell is analyzed, and the results achieved are compared against an existing code.

# NOMENCLATURE

Ai	Area of element i
[B]	Strain-displacement matrix
<sup>c</sup> 1	Distance between neutral axis of a stiffener and the reference surface of the shell.
[D]	Tangent moduli matrix
{e}	Strain vector
{e} <sub>i</sub>	Strain vector in element i
{e <sub>1</sub> },{e <sub>2</sub> },{e <sub>3</sub> },{e <sub>4</sub> }	Strain vectors in the 4 regions within an element; components of vector $\{e_1\}$ .
e <sub>xx</sub> , e <sub>yy</sub> , e <sub>xy</sub>	Components of strain in cartesian coordinates; components of vector $\{e_1\}$ , $\{e_2\}$ , etc.
e <sub>11</sub> , e <sub>22</sub> , e <sub>12</sub>	Components of strain in an orthogonal coordinate system.
F, F <sub>0</sub> , F <sub>L</sub>	Subsequent, initial, and limit yield functions
F <sub>s</sub> , F <sub>M</sub>	Absolute values of the gradients of the yield function F.
{ <b>r</b> } <sub>i</sub>	Force vector of element i
h <sub>1</sub> , h <sub>2</sub>	Metric coefficients
I <sub>N</sub> , I <sub>M</sub> , I <sub>NM</sub>	Stress resultant invariants
k <sub>xx</sub> , k <sub>yy</sub> , k <sub>xy</sub>	Components of curvature within an element, in cartesian coordinates; components of the strain vector $\{e_1\}$ , $\{e_2\}$ etc.
k <sub>11</sub> , k <sub>22</sub> , k <sub>12</sub>	Components of curvature in an orthogonal coordinate system.
L <sub>1</sub>	Distance between stiffeners
M <sub>11</sub> , M <sub>22</sub> , M <sub>12</sub>	Moment per unit length; components of the stress-resultant vector
M <sup>*</sup> <sub>ij</sub>	Strain hardening parameters
N	Total number of elements with the structure.
N <sub>11</sub> , N <sub>22</sub> , N <sub>12</sub>	Normal force per unit length; components of the stress-resultant vector.

{P}	Vector of external forces acting on the nodes
{p}	Surface loading per unit area
{q} <sub>i</sub>	Nodal displacement vector of element i.
R <sub>x</sub> , R <sub>y</sub>	Radii of curvature along the principal directions of the shell in cartesian coordinates.
R <sub>1</sub> , R <sub>2</sub>	Radii of curvature along the principal directions of the shell in orthogonal coordinates.
{s}	Stress-resultant vector
{u}	Displacements of a point within an element.
<sup>u</sup> 1, <sup>u</sup> 2	Tangential displacements; components of the vector $\{u\}$ in section II.
<sup>u</sup> 1, <sup>u</sup> 2, <sup>u</sup> 3, <sup>u</sup> 4	Tangential displacements in the x direction of the 4 nodes contiguous to an element; components of vector $\{q\}$ in section IV.
{v} <sup>n</sup> j	Velocity vector of node j at time step n.
v <sub>1</sub> , v <sub>2</sub> , v <sub>3</sub> , v <sub>4</sub>	Tangential displacements in the y direction of 4 nodes contiguous to an element; component of vector $\{q\}$ in section IV.
w	Normal displacements; components of vector $\{u\}$ in section II.
w <sub>1</sub> , w <sub>2</sub> w <sub>12</sub>	Normal displacements of the 12 nodes around an element; components of vector $\{q\}$ in section IV.
х, у	Cartesian coordinates $x = h_1 \xi_1$ , $y = h_2 \xi_2$
Δt	Time step
Δ <b>x</b> , Δ <b>y</b>	Distance between nodes in cartesian coordinates.
δe	Increment in strain
δu	Increment in displacement
ξ <sub>1</sub> , ξ <sub>2</sub>	Orthogonal coordinates along the principal curvatures.
ρ	Mass density per unit area of shell surface.
φ, φ <sub>1</sub> , φ <sub>2</sub>	Twist, rotations with respect to $\boldsymbol{\xi}_1$ and $\boldsymbol{\xi}_2$ .

#### I INTRODUCTION

This report is part of a combined theoretical-experimental study, under a joint DNA/NAVSEA/ONR program, which is aimed at evaluating and increasing submarine hardness to underwater explosions. Previous reports in the series were aimed primarily at studying shock effects, in the elastic range, on internal equipment. The present report is part of an effort to analyze submarine lethality problems, where large elastoplastic motions of the hull may occur under the action of long duration full envelopment shock loadings, which are produced by nuclear explosions.

The first report in the lethality series, Ref. [1], involves the formulation of an elasto-plastic theory for stiffened shells. The present report describes a numerical procedure for the dynamic analysis of elasto-plastic shells using a direct integration in time. While the examples presented here are for shells in vacuo, the Doubly Asymptotic Approximations (DAA) is currently being implemented into the code in order to treat the fluid interaction problem.

The objectives of this work are the following:

- A realistic modeling of complex shells of arbitrary geometry, including stiffeners and internal structure.
- The analysis of shock phenomena with high frequency components in their spectrum.
- 3) The modeling of elasto-plastic material behavior.
- 4) The capability of taking into account large displacement gradients in order to analyze dynamic buckling conditions and post-buckling behavior.

The realistic modeling of complex structures for shock phenomena results in very large problems, with many degrees of freedom. This fact

and the nonlinearities implied by the conditions (3) and (4) point to a finite element or finite difference method, together with the direct integration in time of the equations of motion, as the most promising approach. The nonlinearities of the problem makes the normal-mode expansion method unsuitable for the present purposes.

A survey of the existing numerical methods of analyzing elastoplastic shells for shock problems, undertaken at the beginning of this work, revealed that additional development was needed. There are several aspects to the existing methods which make them inappropriate in meeting the analysis requirements of the present work. Specifically:

- (a) A refined element, employing high-order approximating functions, has proven to be an efficient approach to the static analysis of shells and the determination of low natural modes and frequencies. The accuracy of such an element allows for the use of larger elements, reducing the total number of degrees of freedom required for the entire shell. In contrast to this, in shock and wave propagation problems, a large number of mass points is the only way of achieving an accurate solution, even if the element itself is relatively simple. It appears that the shell elements with "condensed" stiffness matrices, i.e. with massless and loadless internal nodes eliminated by a static condensation procedure, are especially unsuitable for this purpose.
- (b) The masses associated with the rotational degrees of freedom present in the finite element method are usually very small. This causes numerical difficulties in an explicit scheme. If the "rotational masses" are neglected, the solution consists of the integration in time of the translational degrees of freedom, together with the

solution of a system of "static" equations for the rotational degrees of freedom. Since these equations are nonlinear, their solution (which must be repeated at each step of the integration in time) would require an enormous increase in the number of computations.

(c) For problems involving a structure subject to cyclic loads in the plastic range, the determination of the stress resultants in existing methods is accomplished by first computing the stress components at several locations through the thickenss of the shell, and then computing the stress resultants by numerical integration of the stresses through the thickness of the shell. While the computations involved are simple, the amount of stored data becomes prohibitively large for structures involving many elements.

The approach adopted in the present work is believed to be free from the above mentioned drawbacks. The main aspects of this approach and their current status are discussed in the following sections.

## II BASIC SHELL EQUATIONS

The kinematic equations of the shell theory employed in this work correspond to the Donnell-Vlasov nonlinear theory, with the option open of refining them to achieve Sander's theory. In orthogonal coordinates along the principal curvatures, the strain-displacement relations read

where

$$\phi_{1} = -\frac{\partial w}{h_{1}\partial\xi_{1}} + \frac{u_{1}}{R_{1}} - \frac{u_{2}}{R_{2}}$$

$$\phi_{2} = -\frac{\partial w}{h_{2}\partial\xi_{2}} + \frac{u_{2}}{R_{2}}$$

$$\phi = \frac{1}{2} \frac{1}{h_{1}h_{2}} \left[ \frac{\partial}{\partial\xi_{1}} (h_{2}u_{2}) - \frac{\partial}{\partial\xi_{2}} (h_{1}u_{1}) \right]$$
(2.2)

The underlined terms represent geometric nonlinearities; the terms with broken underlines are those of Sander's theory.

The stress resultants are defined as

$$N_{ij} = \int_{-h/2}^{h/2} s_{ij} dz$$

$$M_{ij} = \int_{-h/2}^{h/2} s_{ij} z dz$$

with i = 1, 2; j = 1, 2.

The theory is completed by writing the equations of equilibrium which, for the present purposes, are assumed in the form of the Principle of Virtual Work. With the notation

$$\{u\} = (u_1, u_2, w)^T$$

$$\{s\} = (N_{11}, N_{22}, N_{12}, M_{11}, M_{22}, M_{12})^T$$

$$\{e\} = (e_{11}, e_{22}, 2e_{12}, k_{11}, k_{22}, 2k_{12})^T$$
with
$$\{p\} = (p_1, p_2, p_3)^T$$

standing for the surface loading. The Principle of Virtual Work reads

$$\int_{S} \{s\}^{T} \{\delta e\} dS - \int_{S} \{p\}^{T} \{\delta u\} dS + \int_{S} \rho \{\ddot{u}\}^{T} \{\delta u\} dS = 0$$
 (2.3)

where  $\rho$  is the mass density per unit area of the shell.

#### III SHELL CONSTITUTIVE EQUATIONS

The shell constitutive equations are the relations between the rates of the stress resultants and the rates of the shell strains. In the matrix notation introduced in the preceeding section, they are

$$\{\dot{\mathbf{s}}\} = [\mathbf{D}] \{\dot{\mathbf{e}}\} \tag{3.1}$$

where [D] is the so-called elasto-plastic tangent stiffness matrix.

The explicit from of the above relation is based on an elastoplastic theory for shells presented in a separate report (Ref. [1]).

The aforementioned theory is analogous to classical theories of plasticity; consisting of a yield condition, a strain hardening rule, and a flow rule. It differs from classical elasto-plastic theories in that the yield surface is defined in terms of the stress resultants {s} instead of the stresses. This avoids the necessity of computing and storing stresses through the thickness of the shell.

The stress components at the top and bottom surfaces of a solid shell can be expressed in terms of the stress resultants as:

$$\sigma_{ij} = \frac{N_{ij}}{h} + \frac{6M_{ij}}{h^2}$$
 (3.2)

where h is the thickness of the shell, and the plus sign applies to the top and the minus sign to the bottom of the shell.

An expression for the initial yield surface is constructed by Substituting expression (3.2) into Mises' yield condition

$$\frac{1}{\sigma_0^2} \left(\sigma_{11}^2 + \sigma_{22}^2 - \sigma_{11} \sigma_{22}^2 + 3 \sigma_{12}^2\right) = 1 \tag{3.3}$$

resulting in

$$F_0 = I_N + I_M + 2 I_{NM} = 1$$
 (3.4)

where

$$I_{N} = \frac{1}{N_{0}^{2}} (N_{11}^{2} + N_{22}^{2} - N_{11}^{2} + 3N_{12}^{2})$$
 (3.5)

$$I_{M} = \frac{1}{M_{0}^{2}} (M_{11}^{2} + M_{22}^{2} - M_{11}^{2} + 3M_{12}^{2})$$
 (3.6)

$$I_{NM} = \frac{1}{N_0 M_0} (N_{11} M_{11} + N_{22} M_{22} - \frac{1}{2} N_{11} N_{22} - \frac{1}{2} N_{22} M_{11} + 3N_{12} M_{12})$$
 (3.7)

and

$$N_0 = \sigma_0 h$$
 ,  $M_0 = \sigma_0 h^2 / 6$  (3.8)

A limit surface is assumed which is also a linear combination of  $\mathbf{I}_{N}$ ,  $\mathbf{I}_{M}$ , and  $\mathbf{I}_{NM}$ . Coefficients for the three terms are determined empirically in order to produce a good approximation for the limit surface. The expression,

$$F_L = I_N + \frac{4}{9} I_M + \frac{2}{3\sqrt{3}} I_{NM}$$
 (3.9)

which represents the limit condition exactly for the three extreme cases of (1) only membrane forces, (2) only bending moments and (3)  $N_{11} = N_{22}$  with  $M_{11} = M_{22}$ , was chosen.

A hardening rule is generated in the following manner. A variable yield surface of the form

$$F \equiv I_N + I_M^* + \alpha I_{NM} = 1$$
 (3.10)

is assumed where

$$I_{M}^{*} = \frac{1}{M_{0}^{2}} [M_{11} - M_{11}^{*}]^{2} + (M_{22} - M_{22}^{*})^{2}$$

$$- (M_{11} - M_{11}^{*}) (M_{22} - M_{22}^{*}) + 3(M_{12} - M_{12}^{*})^{2}]$$
(3.11)

The quantities  $M_{ij}^*$ , which represent "hardening parameters", are defined by the following:

If 
$$F = 1$$
 and  $\frac{\partial F}{\partial N_{ij}} \dot{N}_{ij} + \frac{\partial F}{\partial M_{ij}} \dot{M}_{ij} > 0$ :

$$dM_{ij} = 2(1 - F_L) \frac{M_0}{k_0} \frac{F_s^2}{F_M^2} dk_{ij}^{"}$$

If  $F < 1$  or  $\frac{\partial F}{\partial N_{ij}} \dot{N}_{ij} + \frac{\partial F}{\partial M_{ij}} \dot{M}_{ij} \leq 0$ :
$$dM_{ij}^* = 0$$
(3.12)

The symbols  $F_s$  and  $F_M$  are defined as

$$F_{s} = \left[ \left( N_{0} \frac{\partial F}{\partial N_{11}} \right)^{2} + \left( N_{0} \frac{\partial F}{\partial N_{22}} \right)^{2} + \left( N_{0} \frac{\partial F}{\partial N_{12}} \right)^{2} + \left( N_{0} \frac{\partial F}{\partial N_{12}} \right)^{2} + \left( M_{0} \frac{\partial F}{\partial M_{12}} \right)^{2} + \left( M_{0} \frac{\partial F}{\partial M_{12}} \right)^{2} \right]^{1/2}$$

$$F_{M} = \left[ \left( M_{0} \frac{\partial F}{\partial M_{11}} \right)^{2} + \left( M_{0} \frac{\partial F}{\partial M_{22}} \right)^{2} + \left( M_{0} \frac{\partial F}{\partial M_{12}} \right)^{2} \right]^{1/2}$$
(3.14)

 $\mathbf{F_s}$  is the absolute value of the vector grad  $\mathbf{F}$ , in a dimensionless formulation;  $\mathbf{F_M}$  is the part of grad  $\mathbf{F}$  which corresponds to the bending moments only.

An associated flow rule for the plastic strain rates is assumed of the form:

$$(e_{11}, e_{22}, e_{12}, k_{11}, k_{22}, k_{12}) = \lambda (\frac{\partial F}{\partial N_{11}}, \frac{\partial F}{\partial N_{22}}, \frac{\partial F}{\partial N_{12}}, \frac{\partial F}{\partial M_{11}}, \frac{\partial F}{\partial M_{22}}, \frac{\partial F}{\partial M_{12}})$$
 (3.15)

A more detailed discussion of the theory, along with some numerical results, are presented in Ref. [1].

# IV DISCRETIZATION

The discretization procedure adopted has two aspects in common with the classical finite element method. First, a variational derivation is used for the equations of motion. Second, a quadrilateral element is used, in which the stresses and strains are computed from the nodal displacements of nodes surrounding the element.

A quadrilateral shell element defined by four corner nodes, with each node having three translational and no rotational terms, does not have enough degrees of freedom to represent bending behavior (second derivative terms). In order to have the required additional degrees of freedom, eight nodes not contiguous with the element are also used in computing bending terms (Fig. 1).

Each element accesses twelve nodes and has twenty degrees of freedom; three translational degrees of freedom for each of the four inner nodes, and one degree of freedom (displacement normal to the surface) for each of the eight exterior nodes. Thus, the nodal displacement vector of an element i is

$$\{q\}_{i} = (u_{1}, u_{2}, u_{3}, u_{4}, v_{1}, v_{2}, v_{3}, v_{4}, w_{1}, w_{2}, \dots, w_{12})^{T}$$
 (4.2)

For the purpose of computing the stiffness of an element, the area of the element is divided into four regions (Fig. 2). One set of strains is computed for each of the four regions. The strain in element i is  $\{e\}_i = (\{e_1\}, \{e_2\}, \{e_3\}, \{e_4\})^T$  where  $\{e_1\}$  is the strain in region 1, and  $\{e_1\} = (e_{xx}, e_{yy}, 2e_{xy}, k_{xx}, k_{yy}, 2k_{xy})^T$ .

At the present time, in order to analyze a series of simple check problems, the discretization has been limited to the case of small strains expressed in cartesian coordinates. In this simplest version of shell theory, the strains have the following form:

$$e_{xx} = \frac{\partial u}{\partial x} + \frac{w}{R_x}, \ e_{yy} = \frac{\partial v}{\partial y} + \frac{w}{R_y}, \ e_{xy} = \frac{1}{2} \left[ \frac{\partial u}{\partial y} + \frac{\partial v}{\partial x} \right]$$

$$k_{xx} = \frac{\partial^2 w}{\partial x^2}, \ k_{yy} = \frac{\partial^2 w}{\partial y^2}, \ k_{xy} = \frac{\partial^2 w}{\partial x \partial y}$$
(4.2)

where  $R_{\mathbf{x}}$  and  $R_{\mathbf{y}}$  are the principal radii of curvature of the shell surface.

The discrete approximations to  $\sim$  above expressions, in region 1 of  $A_i$ , are (for equally spaced nodes)

$$\frac{\partial \mathbf{u}}{\partial \mathbf{x}} = \frac{\mathbf{u}_2 - \mathbf{u}_1}{\Delta \mathbf{x}}, \quad \frac{\partial \mathbf{v}}{\partial \mathbf{y}} = \frac{\mathbf{v}_4 - \mathbf{v}_1}{\Delta \mathbf{y}}, \quad \frac{\partial \mathbf{u}}{\partial \mathbf{y}} = \frac{\mathbf{u}_4 - \mathbf{u}_1}{\Delta \mathbf{y}}, \quad \frac{\partial \mathbf{v}}{\partial \mathbf{x}} = \frac{\mathbf{v}_2 - \mathbf{v}_1}{\Delta \mathbf{x}}$$

$$\frac{\partial^2 \mathbf{w}}{\partial \mathbf{x}^2} = \frac{\mathbf{w}_2 - 2\mathbf{w}_1 - \mathbf{w}_5}{\Delta \mathbf{x}^2}, \quad \frac{\partial^2 \mathbf{w}}{\partial \mathbf{y}^2} = \frac{\mathbf{w}_4 - 2\mathbf{w}_1 + \mathbf{w}_6}{\Delta \mathbf{y}^2}$$

$$\frac{\partial^2 \mathbf{w}}{\partial \mathbf{x} \partial \mathbf{y}} = \frac{\mathbf{w}_3 - \mathbf{w}_2 - \mathbf{w}_4 + \mathbf{w}_1}{\Delta \mathbf{x} \Delta \mathbf{y}}$$
(4.3)

Analogous expressions are formed for regions 2, 3 and 4. This process defines a strain-displacement matrix [B] such that

$$\{e\}_{i} = [B]_{i} \{q\}_{i}$$
 (4.4)

The expression for derivatives is basically a staggered finite difference scheme, with first derivatives computed between nodes, and second derivatives at nodes. One should note that there is no displacement function assumed over the element area for the determination of derivatives, as one finds in a classical finite element formulation.

This type of element, which uses non-contiguous nodes, results in an overlapping of adjacent elements. This overlapping produces complications at boundaries similar to those encountered in finite difference formulations, but are absent from finite element formulations. To minimize the difficulties associated with boundaries, the structure is conceptually divided into sheets. Each sheet is a curved section of shell with an arbitrary number of nodes and elements (Fig. 3). The shape of the sheet is limited to a surface that can be described by a smooth continuous function without any interior discontinuities in its slope. The elements within a sheet are limited to a purely rectangular organization (i.e. exactly four elements must be connected to each interior node).

Thus a cylinder with end caps would consist of three sheets; a circular cylindrical sheet, and a sheet for each end cap (Fig. 4). Three sheets are required to specify this structure because of the edge that occurs between the cylinder and the end caps.

By organizing the structure into sheets, all the difficulties associated with boundaries are isolated into a set of artificial nodes around the perimeter of the sheet. When several sheets are connected at an edge, the following conditions are imposed on the nodes along a shared edge:

- 1) Compatability of displacements of nodes along the edge.
- 2) Compatability of rotations of the nodes along the edge.
- 3) Equilibrium of moments at the nodes along an edge.

## V EQUATIONS OF MOTION

With the shell surface divided into N elements  $A_i$ , the Principle of Virtual Work from Section 2 becomes

$$\sum_{i=1}^{i=N} \left[ \int_{A_i} \left\{ \mathbf{s} \right\}_{i}^{T} \left\{ \delta \mathbf{e} \right\}_{i} dA - \int_{A_i} \left\{ \mathbf{p} \right\}_{i}^{T} \left\{ \delta \mathbf{u} \right\} dA + \int_{A_i} \rho \left\{ \ddot{\mathbf{u}} \right\}_{i}^{T} \left\{ \delta \mathbf{u} \right\} dA = 0$$
 (5.1)

If the variations of strain are expressed in terms of the variation of nodal displacements

$$\{\delta \mathbf{e}\}_{i} = [\mathbf{B}]_{i} \{\delta \mathbf{q}\}_{i} \tag{5.2}$$

and with

$$\int_{A_{i}} \{s\}_{i}^{T} [B]_{i} dA = \{F\}_{i}$$
(5.3)

$$\sum_{i=1}^{i=N} \int_{A_i} \{p\}^T \{\delta u\} dA = \{p\}^T \{\delta q\}$$
(5.4)

$$\sum_{i=1}^{i=N} \int_{A_i} \rho\{\ddot{\mathbf{u}}\}^{\mathrm{T}} \{\delta \mathbf{u}\} dA = ([m] \{\ddot{\mathbf{q}}\})^{\mathrm{T}} \{\delta \mathbf{q}\}$$
(5.5)

the Principle of Virtual Work results in the following system of ordinary differential equations

$$[m] \{\ddot{q}\} = -\sum_{i=1}^{i=N} \{F\}_i + \{P\}$$
 (5.6)

In the above equations, {q} is the nodal displacement vector for the structure,[m] is the lumped mass matrix, and {P} represents the vector of external forces acting on the nodes of the structure.

#### VI INTEGRATION IN TIME

An explicit scheme of integration in time has been selected for the following reasons:

- (a) An implicit scheme would require assembly and inversion of large matrices whose elements, in general, change at each step of one integration. This aspect would seriously impair the ability to deal with large problems.
- (b) The more favorable stability of an implicit scheme would not be utilized, since in most shock loading problems the size of the time step is limited by accuracy requirements rather than stability conditions.

The intended incorporation of the method of shell analysis resulting from this work into a program for three-dimensional dynamics of the interacting medium (e.g., TRANAL) provides an additional strong argument for the direct and explicit integration of the equations of motion.

The system of equations for the nodal displacements of the structure, derived in the preceding section, is integrated in time with the following central difference scheme. The velocity of node j at time step n+l is computed by

$$\{\dot{q}\}_{j}^{n+1} = \{\dot{q}\}_{j}^{n} + \frac{\Delta t}{m_{i}} (\{P\}_{j} - \sum_{i} \{F\}_{i})$$

where element forces  $\{F\}_i$  are summed over all elements i framing into node j, m<sub>j</sub> is the mass of the node, and  $\{P\}_u$  are the externally applied forces on the nodes.

#### VII SMALL STIFFENERS

The term "small stiffeners" is applied to relatively small stiffeners whose spacing is small enough to allow for their representation as a continuous additional layer of the shell structure. This assumption is identical to the assumption which leads to the treatment of stiffened shells as orthotropic shells in the theory of elastic shells.

An element of the stiffened shell is conceptually divided into the shell sheet and the stiffener (Fig. 5). The middle surface of the shell sheet remains the reference surface of the stiffened shell. Within the shell sheet, the increment in strain and the increment in stress resultants are computed in the usual manner. That is,

$${de} = [B] {dq}$$
 (7.1)

and

$${ds} = [D] {de}$$
 (7.2)

The total increment of the stress resultants for the stiffened shell is the sum of the stress resultants for the shell sheet and the stress resultants of the stiffeners referred back to the reference surface.

Thus,

$$dN_{11} = (dN_{11})_{sheet} + \frac{1}{L_1} (dN_{11})_{stiff}$$
 (7.4)

$$dM_{11} = (dM_{11})_{sheet} + \frac{1}{L_1} (dM_{11} - c_1 dN_{11})_{stiff}$$
 (7.5)

where  $\mathbf{L}_{1}$  is the distance between small stiffeners.

#### VIII LARGE STIFFENERS

For large stiffeners the element mesh must be arranged in such a way that a mesh line runs along a large stiffener. The stiffener is treated as a distinct curved beam element lying along the mesh line of the shell. The nodal displacement vector for a beam element is

$$\{q\}_{j} = (u_1, u_2, v_1, v_2, w_1, w_2, w_3, w_4)$$
 (8.1)

where  $u_1^{-w_4}$  are shown in Fig. 6. Beam strains are computed from nodal displacements using a reduced set of relations consistent with those used in the shell (Eq. 4.3, 4.4).

From this point, the beam is treated in exactly the same manner as the small stiffener. That is, the strains are referred to the centroid of the beam (Eq.7.3). The stress resultants are computed from the strains, and these resultants are then referred back to the middle surface of the shell. The beam contribution to the nodal forces along  $\{q\}_j$  follows from the principle of virtual work.

$$\left\{\mathbf{F}\right\}_{\mathbf{j}}^{\mathbf{T}} = \int_{\mathbf{S}_{\mathbf{j}}} \left\{\mathbf{N}\right\}_{\mathbf{j}}^{\mathbf{T}} \left[\mathbf{B}\right]_{\mathbf{j}} d\mathbf{S}$$

$$(8.2)$$

#### IX IMPLEMENTATION

The formulation summarized in the preceeding sections is in the process of being incorporated into a comptuer code called SHELPLAS. The present version of SHELPLAS is limited to the small displacement analysis of shells modeled by one sheet of rectangular elements. Stiffeners and elasto-plastic material behavior have been incorporated in this version.

In order to verify the overall approach incorporated in this analysis, some test problems were run and the results obtained were compared against results computed with DYNAPLAS (Ref. [2]).

A circular cylindrical shell with a radius of 16.8125" was modeled as shown in Fig. 7. Forty five elements were used along the length of the shell. Small stiffeners, spaced at 5.625 inches, were modeled as an orthotropic shell. The large stiffeners, spaced at 50.625 inches, were modeled as a single element. The left end of the shell was built in, and the right end was a plane of symmetry.

The model was subject to a triangular load (in time), see Fig. 8, of uniform pressure (in space). The peak pressure was 670 psi, and the duration of the load pulse (.5 millesec.) was close to the period of the breathing mode of the shell (.55 millisec).

A history of hoop stresses  $(\sigma_{\theta})$  at element #28 was plotted in Fig. 8. One can see that there was considerable yielding during the first cycle. Figure 9 is a graph of the displacements versus time from both codes. Peak displacements agree to within less than one percent. Excellent agreement was achieved for all points a sufficient distance from the large stiffeners, as can be seen from a graph of the displaced shape (Fig. 10).

Figures 11 through 13 show displacement histories at the three nodes closest to the large stiffeners. As one approaches the stiffener, the gradient of the moment  ${\tt M}_{\tt X}$  becomes considerably larger. The differences in the results of the two codes, as one approaches the stiffener, were due to the different approximations of  ${\tt M}_{\tt X}$  in the elements of the two codes.

The execution time for both codes was less than 2 minutes.

# X CONCLUSIONS

As mentioned in the introduction, this work is concerned with the inelastic response of submarines under dynamic loadings generated by a nuclear explosion. The complexities involved in modeling submarine hulls with major internal components require that careful consideration be given toward optimizing computer usage in the analysis. To this end, an elastó-plastic shell theory has been developed and reported in Ref. [1]. The present report describes a numerical procedure and a direct integration code which uses the shell theory in the analysis of stiffened cylindrical shell structures.

The excellent agreement achieved in comparison with other codes for the analysis of a series of simple check problems has verified the correctness of the overall approach. For the eventual analysis of the very complex submarine problems, it is felt that the present numerical procedures will prove much more efficient than presently available methods.

The code presented in this report is currently being augmented to include the following aspects:

- (1) Fluid structure interaction using the Doubly Asymptotic Approximation.
- (2) Large displacement capability to study dynamic buckling and postbuckling behavior.
- (3) Complex shell structures with internal components.

It is currently planned that this work will be sufficiently advanced to enable us to make predictions for the experiments on stiffened cylindrical structures which will be conducted in the second half of 1977.

## REFERENCES

- [1] M.P. Bieniek and J.R. Funaro, "Elasto-Plastic Behavior of Plates and Shells", Report No. DNA 3954T, Weidlinger Associates, New York, New York, March 1976.
- [2] P.V. Marcal and J.F. McNamara, "Incremental Stiffness Method for Finite Element Analysis of Nonlinear Dynamic Problems", International Symposium on Numerical and Computer Methods in Structural Mechanics, Urbana, Illinois, September 1971.
- [3] W.E. Haisler, and D.K. Vaughan, "DYNAPLAS II A Finite Element Program for Dynamic Large Deflection, Elasto-Plastic Analysis of Stiffened Shells of Revolution", TEES-2926-73-2 and SLA-73-1106, Texas A & M University, College Station, Texas, October 1973.
- [4] R.W.H. Wu and E.A. Witmer, "Finite-Element Predictions of Transient Elastic-Plastic Large Deflections of Stiffened and/or Unstiffened Rings and Cylindrical Shells", MIT ASRL TR 17-4, M.I.T., Cambridge, Massachusetts, April 1974.
- [5] L.H.N. Lee and J.T. Horng, "Inelastic Response of Ring-Stiffened Cylindrical Shells to External Pressure Shock Waves", Technical Report No. UND-75-1, University of Notre Dame, College of Engineering, Notre Dame, Indiana, March 1975.
- [6] D. Bushnell, "A Strategy for the Solution of Problems Involving Both Large Deflections and Nonlinear Material Behavior", Symposium on Approximations and Numerical Methods for the Study of Inelastic Shells, Georgia Institute of Technology, Atlantic, Georgia, May 1975.
- [7] H.S. Levine, R. Winter, H. Armen, Jr., and A. Pifko, "Application of the Finite Element Method to Inelastic Shell Analysis", Symposium on Approximations and Numerical Methods for the Study of Inelastic Shells, Georgia Institute of Technology, Atlanta, Georgia, May 1975.




FIG. I TYPICAL SHELL ELEMENT




FIG. 2 FOUR STRESS REGIONS WITHIN AN ELEMENT




FIG. 3 A SHEET




FIG.4 A CYLINDER WITH END CAPS




FIG. 5 GEOMETRY OF SMALL STIFFENERS





FIG. 6 LARGE STIFFENERS






FIG. 7 MODEL OF A CYLIDRICAL SHELL




FIG. 8 HOOP STRESSES  $\sigma_{\!m{ heta}}$  AT ELEMENT 28




FIG. 9 DISPLACEMENTS AT NODE 28




FIG. 10 DISPLACED SHAPE AT T = 0.5 MSEC.




FIG. II DISPLACEMENTS AT NODE 39




FIG. 12 DISPLACEMENTS AT NODE 38




FIG. 13 DISPLACEMENTS AT NODE 37

CHIEF OF NAVAL RESEARCH DEPARTMENT OF THE NAVY ARLINGTON, VIRGINIA 22217 ATTN. CODE 474

ATTN. CODE 474
ATTN. CODE 471
ATTN. CODE 222
ATTN. TECHNICAL LIBRARY

( 2 COPIES)

DIRECTOR
ONR BRANCH OFFICE
495 SUMMER STREET
BOSTON, MASSACHUSETTS 02210

DIRECTOR
ONR BRANCH OFFICE
219 S. DEARBORN STREET
CHICAGO: ILLINOIS 60604

DIRECTOR
NAVAL RESEARCH LABORATORY
WASHINGTON: D.C 20390
ATTN: CODE 2629 ( ONRL)

1 6 COPIESI

U. S. NAVAL RESEARCH LABORATORY
WASHINGTON, D.C. 2039G
ATTN. CODE 2627

COMMANDING OFFICER
ONR BRANCH OFFICE
207 WEST 24TH STREET
NEW YORK + NEW YORK 10011

DIRECTOR
ONR BRANCH OFFICE
1030 E. GREEN STREET
PASADENA. CALIFORNIA 91101

DEFENSE DOCUMENTATION CENTER CAMERON STATION ALEXANDRIA VIRGINIA 22314 ATTN. TECH. LIBRARY

(12 COPIES)

COMMANDING OFFICER
U. S. ARMY RESEARCH OFFICE DURHAM
BOX CM. DUKE STATION
DURHAM. NORTH CAROLINA 27706
ATTN. MR. J. J. MURRAY
ATTN. CRD-AA-IP

( 2 COPIES)

COMMANDING OFFICER

AMXMR-ATL

U. S. ARMY MATERIALS RES. AGENCY
WATERTOWN. MASSACHUSETTS 02172

ATTN. MR. R. SHEA

WATERVLIET ARSENAL
MAGGS RESEARCH CENTER
WATERVLIET, NEW YORK 12189
ATTN. DIRECTOR OF RESEARCH
ATTN. TECHNICAL LIBRARY

REDSTONE SCIENTIFIC INFO. CENTER
CHIEF. DOCUMENT SECTION
U. S. ARMY MISSILE COMMAND
REDSTONE ARSENAL. ALABAMA 35809

ARMY R & D CENTER FORT BELVOIR, VIRGINIA 22060

COMMANDING OFFICER AND DIRECTOR
NAVAL SHIP RESEARCH & DEV. CNTR.
WASHINGTON. D.C. 20007

ATTN. CODE 042 (TECH. LIB. BR.)
ATTN. CODE 17 (STRUC. MECH. LAB.)
ATTN. CODE 172

ATTN. CODE 174

ATTN. CODE 177

ATTN. CODE 1800 (APPL. MATH. LAB.)
ATTN. 5412S DR. W. D. SETTE
ATTN. CODE 19 DR. M. M. SEVIK
ATTN. CODE 1901 (DR. M. STRASSBERG)
ATTN. CODE 1945
ATTN. CODE 1962

COMMANDER
NAVAL WEAPONS LABORATORY
DAHLGREN LABORATORY
DAHLGREN VIRGINIA 22448
ATTN. TECHNICAL LIBRARY

NAVAL RESFARCH LABORATORY
WASHINGTON, D.C. 20390
ATTN. CODE 8400
ATTN. CODE 8403A
ATTN. CODE 8410
ATTN. CODE 8442
ATTN. CODE 8442
ATTN. CODE 8440
ATTN. CODE 6300
ATTN. CODE 6390
ATTN. CODE 6380
ATTN. CODE 2027

UNDERSEA EXPLOSION RESEARCH DIV.
NAVAL SHIP R & D CENTER
NORFOLK NAVAL SHIPYARD
PORTSMOUTH, VIRGINIA 23709
ATTN. DR. E. PALMER
ATTN. CODE 780
ATTN. TECHNICAL LIBRARY

NAVAL SHIP R & D CENTER
ANNAPOLIS DIVISION
ANNAPOLIS, MARYLAND 21402
ATTN. CODE 2740 MR. Y. F. WANG
ATTN. CODE 28 MR. R.J. WOLFE
ATTN. CODE 281 MR. R.B. NIEDERBERGER
ATTN. CODE 2814 DR. H. VANDERVELDT

NAVAL UNDERWATER WEAPONS CENTER PASADENA ANNEX 3202 E. FOOTHILL BLVD. PASADENA, CALIFORNIA 91107 ATTN. TECHNICAL LIBRARY

CHIEF OF NAVAL MATERIAL NAVY DEPT WASHINGTON D.C. 20360 ATTN MAT 0323

COMMANDER
NAVAL ELECTRONIC SYSTEMS COMMAND
NAVAL ELECTRONIC SYSTEMS COMMAND HQS
WASHINGTON D.C. 20360
ATTN PME 117-21A

SUPERINTENDENT
NAVAL POSTGRADUATE SCHOOL
MONTEREY CA 93940
ATTN CODE 2124 TECH RPTS LIBRARIAN

COMMANDER
NAVAL SEA SYSTEMS COMMAND
NAVY DEPARTMENT
WASHINGTON D.C. 20362
ATTN ORD - 91313 LIB
ATTN CODE 03511 C POHLER

COMMANDER
NAVAL SHIP RESEARCH AND DEV CENTER
BETHESDA MD 20034

ATTN CODE 17 WW MURRAY
ATTN CODE 142-3 LIBRARY
ATTN CODE 174 R SHORT
ATTN CODE 11
ATTN CODE 2740 Y WANG
ATTN CODE 1962
ATTN CODE 1903
ATTN CODE 1731C
ATTN CODE 1171
ATTN CODE 19

COMMANDER
NAVAL SURFACE WEAPONS CENTER
WHITE OAK
SILVER SPRING MD 20910
ATTN CODE 241 J PETES
ATTN CODE 1224 NAVY NUC PRGMS OFF
ATTN CODE 730 TECH LIB
ATTN CODE 240 H SNAY
ATTN CODE 243 G YOUNG

COMMANDING OFFICER
NAVAL WEAPONS EVALUATION FACILITY
KIRTLAND AIR FORCE BASE
ALBUQUERQUE NM 87117
ATTN TECHNICAL LIBRARY

DIRECTOR
STRATEGIC SYSTEMS PROJECTS OFFICE
NAVY DEPARTMENT
WASHINGTON D C 20376
ATTN NSP-272
ATTN NSP-43 TECH LIB

U. S. NAVAL WEAPONS CENTER
CHINA LAKE. CALIFORNIA 93555
ATTN. CODE 4062 MR. W. WERBACK
ATTN. CODE 4520 MR. KEN BISCHEL
ATTN. CODE 533 TECH LIB

COMMANDING OFFICER
U. S. NAVAL CIVIL ENGR. LAB.
PORT HUENEME, CALIFORNIA 93041
ATTN. CODE L31
ATTN. R. ODELLO
ATTN. TECHNICAL LIBRARY

TECHNICAL DIRECTOR
U. S. NAVAL ORDNANCE LABORATORY
WHITE OAK
SILVER SPRING, MARYLAND 20910

TECHNICAL DIRECTOR NAVAL UNDERSEA R & D CENTER SAN DIEGO, CALIFORNIA 92132

SUPERVISOR OF SHIPBUILDING
U. S. NAVY
NEWPORT NEWS. VIRGINIA 23607

TECHNICAL DIRECTOR
MARE ISLAND NAVAL SHIPYARD
VALLEJO, CALIFORNIA 94592

U. S. NAVY UNDERWATER SOUND REF. LAB.
OFFICE OF NAVAL RESEARCH
P. O. BOX 8337
ORLANDO: FLORIDA 32806

CHIEF OF NAVAL OPERATIONS
DEPARTMENT OF THE NAVY
WASHINGTON, D.C. 20350
ATTN. CODE OP-07T
ATTN. CODE OP-03FG
ATTN. OP-985F

STRATEGIC SYSTEMS PROJECT OFFICE DEPARTMENT OF THE NAVY WASHINGTON, D.C. 20390 ATTN. NSP-001 CHIEF SCIENTIST

DEEP SUBMERGENCE SYSTEMS
NAVAL SHIP SYSTEMS COMMAND
DEPARTMENT OF THE NAVY
WASHINGTON. D.C. 20360
ATTN. CODE 39522

ENGINEERING DEPT.
U. S. NAVAL ACADEMY
ANNAPOLIS, MARYLAND 21402

NAVAL AIR SYSTEMS COMMAND
DEPT. OF THE NAVY
WASHINGTON. D.C. 20360
ATTN. NAVAIR 5302 AERO.&STRUC.
ATTN. NAVAIR 5308 STRUCTURES
ATTN. NAVAIR 52031F MAT.
ATTN. NAVAIR 604 TECH. LIBRARY

DIRECTOR. AERO MECHANICS DEPT.
NAVAL AIR DEVELOPMENT CENTER
JOHNSVILLE
WARMINISTER. PENNSYLVANIA 18974

TECHNICAL DIRECTOR

U. S. NAVAL UNDERSEA R&D CENTER

SAN DIEGO: CALIFORNIA 92152

ATTN. TECHNICAL LIBRARY

ENGINEERING DEPARTMENT
U. S. NAVAL ACADEMY
ANNAPOLIS: MARYLAND 21402

NAVAL FACILITIES ENGINEERING COMMAND DEPT. OF THE NAVY WASHINGTON D.C. 20360 ATTN. NAVFAC 03 RES.&DEV. ATTN. NAVFAC 04 RES.&DEV. ATTN. NAVFAC 14114 TECH. LIB.

NAVAL SEA SYSTEMS COMMAND DEPT. OF THE NAVY WASHINGTON. D.C. 20360

> ATTN. NSHIP 03 RES.GTECH. ATTN. NSHIP 031 CH. SCIENTIST FOR R & D ATTN. NSHIP 03412 HYDROMECHANICS

ATTN. NSHIP 037 SHIP SILENCING DIV.

ATTN. NSHIP 035 WEAPONS DYN.

NAVAL SHIP ENGINEERING CENTER PRINCE GEORGE PLAZA HYATTSVILLE, MARYLAND 20782

ATTN. NSEC 6100 SHIP SYS.ENGR.& DES.DEP.

ATTN. NSEC 6102C COMPUTER-AIDED SHIP DES. ATTN. NSEC 6105

ATTN. NSEC 6105C1

ATTN. NSEC 6105G

ATTN. NSEC 6110 SHIP CONCEPT DESIGN

ATTN. NSEC 6110.01

ATTN. NSEC 6120 HULL DIV.

ATTN. NSEC 6120D HULL DIV.

ATTN. NSEC 6128 SURFACE SHIP STRUCT. ATTN. NSEC 6129 SUBMARINE STRUCT.

ATTN. TECHNICAL LIBRARY

ASSISTANT TO THE SECRETARY DEFENSE ATOMIC ENERGY WASHINGTON . DC 20301 ATTN DONALD COTTER

DIRECTOR DEFENSE ADVANCED RSCH PROJ AGENCY ARCHITECT BUILDING 1400 WILSON BLVD ARLINGTON VA. 22209 ATTN A TACHMINDJI ATTN STO KENT KRESA ATTN TECHNICAL LIBRARY ATTN R CHAPMAN

DEFENSE DOCUMENT CENTER CAMERON STATION ALEXANDRIA, VA 22314 ATTN TECH. LIBRARY

( 3 COPIES)

DIRECTOR
DEFENSE INTELLIGENCE AGENCY
WASHINGTON D.C. 20301
ATTN DI-7D E. OFARRELL
ATTN DI-7E
ATTN DT-1C J. VERONA
ATTN DT-2 WPNS + SYS DIV
ATTN TECHNICAL LIBRARY

CHAIRMAN
DEPT OF DEFENSE EXPLO SAFETY BOARD
RM-GB270+ FORRESTAL BUILDING
WASHINGTON D.C. 20301
ATTN DD/S+SS

DIR OF DEFENSE RSCH + ENGINEERING WASHINGTON D.C. 20301
ATTN AD/SW
ATTN DD/TWP
ATTN DD/S+SS
ATTN AD/NP

COMMANDER
FIELD COMMAND
DEFENSE NUCLEAR AGENCY
KIRTLAND AFB. NM 87115
ATTN FCTA
ATTN FCTA-D

INTERSERVICE NUCLEAR WEAPONS SCHOOL KIRTLAND AFB, NM 87115 ATTN TECH LIB DIRECTOR
JOINT STRAT TGT PLANNING STAFF JCS
OFFUTT AFB
OMAHA+ NB 68113
ATTN STINFO LIBRARY

WEAPONS SYSTEMS EVALUATION GROUP 400 ARMY NAVY DRIVE ARLINGTON VA 22202 ATTN DOC CON

CHEIF OF RES. DEV + ACQUISITION
DEPARTMENT OF THE ARMY
WASHINGTON D.C. 20310
ATTN TECHNICAL LIBRARY
ATTN DAMA-CSM-N LTC E. DEBOESER JR

COMMANDER
HARRY DIAMOND LABORATORIES
WASHINGTON D.C. 20438
ATTN AMXDO-NP
ATTN AMXDO-TI TECH LIB

DIRECTOR
U S ARMY BALLISTIC RESEARCH LABS
ABERDEEN PROVING GROUND, MD 21005
ATTN TECH LIB E. BAICY

COMMANDER
U S ARMY COMM COMMMAND
FORT HUACHUCA: AZ 85613
ATTN TECHNICAL LIBRARY

COMMANDER
U S ARMY MAT + MECHANICS RSCH CTR
WATERTOWN. MA 02172
ATTN R SHEA

COMMANDER
U S ARMY NUCLEAR AGENCY
FORT BLISS. TX 79916
ATTN TECH LIB

AF CAMBRIDGE RSCH LABS, AFSC L.G. HANSCOM FIELD BEDFORD MA 01730 ATTN SUOL AFCRL RSCH LIB

HEADQUARTERS
AIR FORCE SYSTEMS COMMAND
ANDREWS AFB
WASHINGTON D C 20331
ATTN TECHNICAL LIBRARY

COMMANDER
ARMAMENT DEVELOPMENT&TEST CENTER
ELGIN AFB FL 32542
ATTN TECHNICAL LIBRARY

LOS ALAMOS SCIENTIFIC LAB
P O BOX 1663
LOS ALAMOS NM 87544
ATTN DOC CONTROL FOR REPORTS LIB

SANDIA LABS LIVERMORE LAB P O BOX 969 LIVERMORE CA 94550 ATTN DOC CON FOR TECH LIB SANDIA LABORATORIES
P.O. BOX 5800
ALBUQUERQUE NM 87115
ATTN DOC CON FOR 3141 SANDIA RPT COLL

U S ENERGY RSCH & DEV ADMIN
DIVISION OF HEADQUARTERS SERVICES
LIBRARY BRANCH G-043
WASHINGTON D C 20545
ATTN DOC CONTROL FOR CLASS TECH LIB

UNIV OF CALIFORNIA LAWRENCE LIVERMORE LAB P.O. BOX 808 LIVERMORE CA 94550 ATTN TECHNICAL LIBRARY

AGBABIAN ASSOCIATES 250 NORTH NASH STREET EL SUGONDO CA 90245 ATTN M AGBABIAN

BATTELLE MEMORIAL INSTITUTE 505 KING AVENUE COLUMBUS OH 43201 ATTN TECHNICAL LIBRARY

BELL TELEPHONE LABORATORIES INC.
MOUNTAIN AVE
MURRAY HILL NJ 07974
ATTN TECH RPT CTR

BOEING COMPANY
P.O. BOX 3707
SEATTLE WA 98124
ATTN AEROSPACE LAB

CAMBRIDGE ACOUSTICAL ASSOC 1033 MASSACHUSETTS AVE CAMBRIDGE MA 02138 ATTN M JUNGER

CIVIL / NUCLEAR SYSTEMS CORP 1200 UNIVERSITY N. F. ALBUQUERQUE NM 87102 ATTN T DUFFY

ELECTRIC BOAT DIV GENERAL DYNAMICS CORP. GROTON CN 06340 ATTN L. CHEN

GENERAL ELECTRIC CO.
TEMPO-CENTER FOR ADVANCED STUDIES
816 STATE STREET (P.O. DRAWER QQ)
SANTA BARBARA CA 93102
ATTN DASIAC

ITT RESEARCH INST 10 WEST 35TH ST CHICAGO IL 60616 ATTN TECHNICAL LIBRARY

INST FOR DEFENSE ANALYSIS 400 ARMY NAVY DRIVE ARLINGTON VA 22202 ATTN IDA LIBRARIAN R SMITH

J.L. MERRITT
CONSULTING + SPECIAL ENGR SVS INC
P.O. BOX 1206
REDLANDS CA 92373
ATTN TECHNICAL LIBRARY

KAMAN AVIDYNE
DIV OF KAMAN SCEINCES CORP
83 SECOND AVE
NW INDUSTRIAL PARK
BURLINGTON MA 01803
ATTN E CRISCIONE
ATTN TECHNICAL LIBRARY
ATTN G ZARTARIAN

KAMAN SCIENCES CORP.
P.O. BOX 7463
COLORADO SPRINGS CO 80933
ATTN TECHNICAL LIBRARY

LOCKHEED MISSILES AND SPACE CO.
3251 HANOVER ST
PALO ALTO CA 94304
ATTN TECH INFO CTR D/COLL
ATTN T GEERS D/52-33 BLDG 205

NATHAN M. NEWMARK
CONSULTING ENGINEERING SERVICES
1114 CIVIL ENGINEERING BLDG
URBANA IL 61801
ATTN N NEWMARK

R+D ASSOCIATES
P.O. BOX 3580
SANTA MONICA CA 90403
ATTN TECHNICAL LIBRARY

STANFORD RESEARCH INST
333 RAVENSWOOD AVE
MENLO PARK CA 94025
ATTN SRT LIB ROOM G021
ATTN B GASTEN
ATTN G ABRAHAMSON

TETRA TECH INC.
630 N ROSEMEAD BLVD
PASEDENA CA 91107
ATTN LI-SAN HWANG
ATTN TECH LIB

THE BDM CORP
1920 ALINE AVE
VIENNA VA 22180
ATTN TECH LIB

URS RESEARCH CO. 155 BOVET RD. SAN MATEO CA 94402 ATTN TECH LIB

TELEDYNE BROWN ENG.
MAIL STOP 44
300 SPARKMAN DRIVE
RESEARCH PARK
HUNTSVILLE, ALABAMA 35807
ATTN DR. MANU PATEL

DIRECTOR
U S ARMY WATERWAYS EXPERIMENT STN
P.O. BOX 631
VICKSBURG MS 39180
ATTN J STRANGE
ATTN W FLATHAU
ATTN TECH LIB (UNCL ONLY)

AF INSTITUTE OF TECHNOLOGY. AU
WRIGHT PATTERSON AFB. OH 45433
ATTN LIB AFIT BLDG 640 AREA B(UNCL ONLY)

COMMANDER WADD
WRIGHT-PATTERSON AIR FORCE BASE
DAYTON, OHIO 45433

ATTN. CODE WWRMDD
ATTN. CODE AFFDL (FDDS)
ATTN. CODE STRUCTURES DIVISION
ATTN. CODE AFLC (MCEEA)

CHIEF. APPLIED MECHANICS GROUP U. S. AIR FORCE INST. OF TECH. WRIGHT-PATTERSON AIR FORCE BASE DAYTON. OHIO 45433

CHIEF, CIVIL ENGINEERING BRANCH WLRC, RESEARCH DIVISION AIR FORCE WEAPONS LABORATORY KIRTLAND AFB, NEW MEXICO 87117

AIR FORCE OFFICE OF SCIENTIFIC RES.
1400 WILSON BOULEVARD
ARLINGTON. VIRGINIA 22209
ATTN. MECHS. DIV.

STRUCTURES RESEARCH DIVISION
NATIONAL AERONAUTICS & SPACE ADMIN.
LANGLEY RESEARCH CENTER
LANGLEY STATION
HAMPTON. VIRGINIA 23365

NATIONAL AERONAUTICS & SPACE ADMIN. ASSOCIATE ADMINISTRATOR FOR ADVANCED RESEARCH & TECHNOLOGY WASHINGTON. D.C. 20546 SCIENTIFIC & TECH. INFO. FACILITY NASA REPRESENTATIVE (S-AK/DL) P. O. BOX 5700 BETHESDA, MARYLAND 20014

COMMANDANT
CHIEF, TESTING & DEVELOPMENT DIV.
U. S. COAST GUARD
1300 E STREET, N. W.
WASHINGTON, D.C. 20226

TECHNICAL DIRECTOR
MARINE CORPS DEV. & EDUC. COMMAND
QUANTICO, VIRGINIA 22134

DIRECTOR
NATIONAL BUREAU OF STANDARDS
WASHINGTON, D.C. 20234
ATTN. MR. B. L. WILSON, EM 219

NATIONAL SCIENCE FOUNDATION ENGINEERING DIVISION WASHINGTON + D.C. 20550

SCIENCE & TECH. DIVISION LIBRARY OF CONGRESS WASHINGTON, D.C. 20540 DIRECTOR
DEFENSE NUCLEAR AGENCY
WASHINGTON D.C. 20350

ATTN. DDST ATTN. SPSS ATTN. STST AR

ATTN. STST ARCHIVES
ATTN. STTL TECHNICAL LIBRARY

( 2 COPIES)

1 2 COPIESI

COMMANDER FIELD COMMAND DEFENSE NUCLEAR AGENCY SANDIA BASE ALBUQUERQUE, NEW MEXICO 87115

DIRECTOR DEFENSE RESEARCH & ENGRG.
TECHNICAL LIBRARY
ROOM 3C-128
THE PENTAGON
WASHINGTON, D.C. 20301

CHIEF, AIRFRAME & EQUIPMENT BRANCH FS-120 OFFICE OF FLIGHT STANDARDS FEDERAL AVIATION AGENCY WASHINGTON, D.C. 20553

DEPUTY CHIEF. OFFICE OF SHIP CONSTR.

MARITIME ADMINISTRATION

WASHINGTON. D.C. 20235

ATTN. MR. U. L. RUSSO

DIV. OF REACTOR DEV. & TECHNOLOGY ATOMIC ENERGY COMMISSION GERMANTOWN. MARYLAND 20767 SHIP HULL RESEARCH COMMITTEE NATIONAL RESEARCH COUNCIL NATIONAL ACADEMY OF SCIENCES 2101 CONSTITUTION AVENUE WASHINGTON, D.C. 20418
ATTN. MR. A. R. LYTLE

DR. J. TINSLEY ODEN
UNIVERSITY OF TEXAS AT AUSTIN
345 ENG. SCIENCE BLDG.
AUSTIN, TEXAS 78712

PROFESSOR JULIUS MIKLOWITZ DIV. OF ENGINEERING & APPLIED SCI. CALIFORNIA INSTITUTE OF TECHNOLOGY PASADENA. CALIFORNIA 91109

DR. HAROLD LIEBOWITZ. DEAN SCHOOL OF ENGR. & APPLIED SCIENCE GEORGE WASHINGTON UNIVERSITY 725 23RD STREET WASHINGTON. D.C. 20006

PROFESSOR ELI STERNBERG DIV. OF ENGR. & APPLIED SCIENCES CALIFORNIA INSTITUTE OF TECHNOLOGY PASADENA. CALIFORNIA 91109

PROFESSOR PAUL M. NAGHDI DIV. OF APPLIED MECHANICS ETCHEVERRY HALL UNIVERSITY OF CALIFORNIA BERKELEY. CALIFORNIA 94720 PROFESSOR P. S. SYMONDS BROWN UNIVERSITY DIVISION OF ENGINEERING WASHINGTON, D. C. 20017

PROFESSOR A. J. DURELLI CIVIL/MECHANICAL ENGINEERING THE CATHOLIC UNIV. OF AMERICA WASHINGTON. D.C. 20017

PROFESSOR R. B. TESTA
DEPT. OF CIVIL ENGINEERING
COLUMBIA UNIVERSITY
S. W. MUDD BLDG.
NEW YORK NEW YORK 10027

PROFESSOR H. H. BLEICH
DEPARTMENT OF CIVIL ENGINEERING
COLUMBIA UNIVERSITY
AMSTERDAM & 120TH STREET
NEW YORK. NEW YORK 10027

PROFESSOR F. L. DIMAGGIO
DEPARTMENT OF CIVIL ENGINEERING
COLUMBIA UNIVERSITY
616 MUDD BUILDING
NEW YORK. NEW YORK 10027

PROFESSOR A. M. FREUDENTHAL GEORGE WASHINGTON UNIVERSITY SCHOOL OF ENGRG. & APPLIED SCIENCE WASHINGTON. D.C. 20006 D. C. EVANS
UNIVERSITY OF UTAH
COMPUTER SCIENCE DIVISION
SALT LAKE CITY, UTAH 84112

PROFESSOR NORMAN JONES
MASSACHUSETTS INST. OF TECHNOLOGY
DEPT. OF NAVAL ARCH. & MARINE ENGRG.
CAMBRIDGE. MASSACHUSETTS 02139

DR. V. R. HODGSON WAYNE STATE UNIVERSITY SCHOOL OF MEDICINE DETRIOT, MICHIGAN 48202

PROFESSOR B. A. BOLEY NORTHWESTERN UNIVERSITY TECHNOLOGICAL INSTITUTE 2145 SHERIDAN ROAD EVANSTON: ILLINOIS 60201

PROFESSOR P. G. HODGE UNIVERSITY OF MINNESOTA DEPT. AEROSPACE ENG. & MECH. MINNEAPOLIS. MINNESOTA 55455

DR. D. C. DRUCKER
DEAN OF ENGINEERING
UNIVERSITY OF ILLINOIS
URBANA, ILLINOIS 61801

PROFESSOR E. REISSNER
UNIVERSITY OF CALIFORNIA. SAN DIEGO
DEPARTMENT OF APPLIED MECHANICS
LA JOLLA. CALIFORNIA 92037

PROFESSOR WILLIAM A. NASH
DEPT. OF MECHS. & AEROSPACE ENGRG.
UNIVERSITY OF MASSACHUSETTS
AMHERST. MASSACHUSETTS 01002

LIBRARY (CODE 0384)
U. S. NAVAL POSTGRADUATE SCHOOL
MONTERY: CALIFORNIA 93940

PROFESSOR ARNOLD ALLENTUCH DEPT. OF MECHANICAL ENGINEERING NEWARK COLLEGE OF ENGINEERING 323 HIGH STREET NEWARK. NEW JERSEY 07102

DR. GEORGE HERRMANN STANFORD UNIVERSITY DEPT. OF APPLIED MECHANICS STANFORD. CALIFORNIA 94305

PROFESSOR J. D. ACHENBACH NORTHWESTERN UNIVERSITY DEPT. CIVIL ENGINEERING EVANSTON. ILLINOIS 60201 DIRECTOR. APPLIED RESEARCH LAB.
PENNSYLVANIA STATE UNIVERSITY
P. O. BOX 30
STATE COLLEGE. PENNSYLVANIA 16801

PROFESSOR EUGENE J. SKUDRZYK
APPLIED RESEARCH LAB.
DEPARTMENT OF PHYSICS
PENNSYLVANIA STATE UNIVERSITY
P. O. BOX 30
STATE COLLEGE, PENNSYLVANIA 16801

PROFESSOR J. KEMPNER
DEPT. OF AERO. ENGR.& APPLIED MECHS.
POLYTECHNIC INSTITUTE OF BROOKLYN
333 JAY STREET
BROOKLYN, NEW YORK 11201

PROFESSOR J. KLOSNER
POLYTECHNIC INSTITUTE OF BROOKLYN
DEPT. OF AEROSPACEGAPPL. MECH.
333 JAY STREET
BROOKLYN. NEW YORK 11201

PROFESSOR R. A. SCHAPERY CIVIL ENGRG. DEPARTMENT TEXAS A & M UNIVERSITY COLLEGE STATION: TEXAS 77840 PROFESSOR W. D. PILKEY
DEPT. OF AEROSPACE ENGRG.
UNIVERSITY OF VIRGINIA
CHARLOTTESVILLE. VIRGINIA 22903

DR. H. G. SCHAEFFER
UNIVERSITY OF MARYLAND
AEROSPACE ENG. DEPT.
COLLEGE PARK. MARYLAND 20752

PROFESSOR K. D. WILLMERT CLARKSON COLLEGE OF TECHNOLOGY DEPT. OF MECHANICAL ENG. POTSDAM. N. Y. 13676

DR. J. A. STRICKLIN TEXAS A&M UNIVERSITY AEROSPACE ENG. DEPT. COLLEGE STATION. TEXAS 77843

DR. L. A. SCHMIT UNIV. OF CALIF. L. A. SCHOOL ENG. EAPPL. SCIENCE LOS ANGELES. CALIF. 90024

DR. H. A. KAMEL
THE UNIVERSITY OF ARIZONA
AEROSPACE &MECH. ENG. DEPT.
TUCSON, ARIZONA 85721

DR. B. S. BERGER
UNIVERSITY OF MARYLAND
DEPT. CIVIL ENGINEERING
COLLEGE PARK. MARYLAND 20742

PROFESSOR G. R. IRWIN
DEPT. MECHANICAL ENG.
UNIVERSITY OF MARYLAND
COLLEGE PARK. MARYLAND 20742

DR. S. J. FENVES
CARNEGIE-MELLON UNIVERSITY
DEPT. CIVIL ENG.
SCHENLEY PARK
PITTSBURGH. PENNA. 15213

DR. RONALD L. HUSTON
DEPT. OF ENG. ANALYSIS
MAIL BOX 112
UNIVERSITY OF CINCINNATI
CINCINNATI, OHIO 45221

PROFESSOR G. SIH
DEPT. OF MECHANICS
LEHIGH UNIVERSITY
BETHLEHEM. PENNA. 18015

PROFESSOR ALBERT S. KOBAYASHI DEPT. OF MECHANICAL ENGRG. UNIVERSITY OF WASHINGTON SEATTLE. WASHINGTON 98105 LIBRARIAN
WEBB INSTITUTE OF NAVAL ARCH.
CRESCENT BEACH ROAD
GLEN COVE. L.I.. NEW YORK 11542

DR. DANIEL FREDERICK
DEPT. OF ENGR. MECHS.
VIRGINIA POLYTECHNIC INST.
BLACKSBURGH. VIRGINIA 24061

PROFESSOR A. C. ERINGEN DEPT. ENG. MECHANICS PRINCETON UNIVERSITY PRINCETON, N. J. 08540

DR. S. L. KOH SCHOOL OF AERO.ASTRO.ENG. SC. PURDUE UNIVERSITY LAFAYETTE, INDIANA 47907

PROFESSOR E. H. LEE DIV. OF ENGR. MECHANICS STANFORD UNIVERSITY STANFORD, CALIFORNIA 94305

PROFESSOR R. D. MINDLIN DEPT. CIVIL ENG. COLUMBIA UNIVERSITY S. W. MUDD BLDG. NEW YORK. N. Y. 10027 PROFESSOR S. B. DONG
UNIVERSITY OF CALIFORNIA
DEPARTMENT OF MECHANICS
LOS ANGELES. CALIFORNIA 90024

PROFESSOR B. PAUL UNIVERSITY OF PENNSYLVANIA TOWNE SCHOOL CIVIL&MECH. ENG. RM. 113 - TOWNE BLDG. 220 S. 33 STREET PHILADELPHIA. PENNA. 19104

PROFESSOR LIU
DEPT. CHEMICAL ENG. & METAL.
SYRACUSE UNIVERSITY
SYRACUSE. N. Y. 13210

PROFESSOR S. BODNER TECHNION RGD FOUNDATION HAIFA. ISRAEL

PROFESSOR R. J. H. BOLLARD CHAIRMAN, AERONAUTICAL ENGRG. DEPT. 207 GUGGENHEIM HALL UNIVERSITY OF WASHINGTON SEATTLE, WASHINGTON 98105

PROFESSOR G. S. HELLER BROWN UNIVERSITY DIVISION OF ENGINEERING PROVIDENCE, RHODE ISLAND 02912 PROFESSOR W. GOLDSMITH
DEPT. MECHANICAL ENG.
DIVISION APPLIED MECHANICS
UNIVERSITY OF CALIFORNIA
BERKELEY. CALIF. 94720

PROFESSOR J. R. RICE DIV. OF ENGINEERING BROWN UNIVERSITY PROVIDENCE. RHODE ISLAND 02912

PROFESSOR R. S. RIVLIN CENTER APPL. OF MATH. LEHIGH UNIVERSITY BETHLEHEM, PENNSYLVANIA 18015

DR. F. COZZARELLI
DIV. INTER. STUDIES&RESEARCH
SCHOOL OF ENGINEERING
STATE UNIV. OF NEW YORK
BUFFALO, N. Y. 14214

LIBRARY SERVICES DEPARTMENT REPORT SECTION: BLDG: 14-14 ARGONNE NATIONAL LABORATORY 9700 S: CASS AVENUE ARGONNE: ILLINOIS 60440

DR. M. C. JUNGER
CAMBRIDGE ACOUSTICAL ASSOCIATES
129 MOUNT AUBURN STREET
CAMBRIDGE, MASSACHUSETTS 02138

DR. L. H. CHEN
GENERAL DYNAMICS CORPORATION
ELECTRIC BOAT DIVISION
GROTON, CONNECTICUT 06340

DR. JOSHUA E. GREENSPON
J. G. ENGR. RESEARCH ASSOCIATES
3831 MENLO DRIVE
BALTIMORE. MARYLAND 21215

DR. S. BATDORF
THE AEROSPACE CORP.
P.O. BOX 92957
LOS ANGELES. CALIF. 90009

DR. K. C. PARK
LOCKHEED PALO ALTO RES. LAB.
DEPT. 5233. BLDG. 205
3251 HANOVER STREET
PALO ALTO. CALIF. 94304

LIBRARY NEWPORT NEWS SHIPBUILDING & DRY DOCK COMPANY NEWPORT NEWS, VIRGINIA 23607

DR. W. F. BOZICH
MC DONNEL DOUGLAS CORP.
5301 BOLSA AVE.
HUNTINGTON BEACH. CALIF. 92647

DR. H. N. ABRAMSON SOUTHWEST RESEARCH LAB. TECHNICAL VICE PRESIDENT MECHANICAL SCIENCES P. O. DRAWER 28510 SAN ANTONIO, TEXAS 78284

DR. R. C. DE HART
SOUTHWEST RESEARCH INSTITUTE
DEPT. OF STRUCTURAL RESEARCH
P.O. DRAWER 28510
SAN ANTONIO, TEXAS 78206

DR. W. A. VON RIESMANN
SANDIA CORPORATION
SANDIA BASE
ALBUQUERQUE. NEW MEXICO 87115

DR. T. L. GEERS
LOCKHEED MISSLES & SPACE CO.
PALO ALTO RESEARCH LAB.
3251 HANOVER ST.
PALO ALTO, CALIFORNIA 94302

WEIDLINGER ASSOCIATES
3000 SAND HILL ROAD
BUILDING 4 SUITE 245
MENLO PARK CA 94025
ATTN J. ISENBERG

WEIDLINGER ASSOCIATES
110 EAST 59TH STREET
NEW YORK NY 10022
ATTN DR. M. BARON

DR. J. L. TOCHER

ROEING COMPUTER SERVICES. INC.

P.O. BOX 24346

SEATTLE. WASHINGTON 98124

MR. W. CAYWOOD CODE BBE. APPL. PHYSICS LAB. 8621 GEORGIA AVE. SILVER SPRINGS. MARYLAND 20034

MR. P. C. DURUP LOCKHEED-CALIF. CO. AEROMECHANICS DEPT., 74-43 BURBANK, CALIF. 91503

	ON PAGE	READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER	2. GOVT ACCESSION NO	. 3. RECIPIENT'S CATALOG NUMBER
TITLE (and Subtitie)		TYPE OF REPORT & PERIOD COVERE
NUMERICAL ANALYSIS OF THE DYNAM ELASTO-PLASTIC SHELLS.	IC RESPONSE OF	TECHNICAL REPORT NO. 20
E 2	The state of the s	B. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(e)	CONTRACTOR	B. CONTRACT OR GRANT NUMBER(a)
M.P. Bieniek, J. Funaro and M.L.	./Baron 5	NØ0014-72-C-0119
PERFORMING ORGANIZATION NAME AND ADD	RESS	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
Weidlinger Associates 110 East 59th Street		
New York, New York 10022		
1. CONTROLLING OFFICE NAME AND ADDRESS		127 BEPORT DATE
Department of the Navy		(//) NOVER 276 /
Office of Naval Research		13. NUMBER OF PAGES
Arlington, Virginia 22217		30
14. MONITORING AGENCY NAME & ADDRESS(II dil	lierent from Controlling Office)	15. SECURITY CLASS. (of this report)
	(12)	UNCLASSIFIED
	4690	15a. DECLASSIFICATION/DOWNGRADING
	1 1	SCHEDULE
7. DISTRIBUTION STATEMENT (of the abetract and	dered in Block 20, If different fro	om Report)
8. SUPPLEMENTARY NOTES		
Shells Plasticity Dynamic Analysis	ary and identify by block number	)
20. ABSTRACT (Continue on reverse side if necessar	ry and identify by block number)	

DD 1 JAN 73 1473

EDITION OF 1 NOV 65 IS OBSOLETE S/N 0102-014-6601 |

UNCLASSIFIED
SECURITY CLASSIFICATION OF THIS PAGE (When Date Entered)

313050



CURITY CLASSIFICATION OF THIS PAGE(When Date Entered)	
	•